
Subject: Re: STATA code for replicating table 2.4 in BHFS 2017

Posted by [SaraDHS](#) on Thu, 08 Jul 2021 16:44:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

Greetings Rubyath,

In order to recreate table 8.1 in the final report, you can use the code below.

use "BDPV7IFLSP.DTA", clear //the Provider file, which has the training variables

*training in the past 24 months

gen diab_train_24=0

replace diab_train_24=1 if p207==1 & p208==1

*training ever

gen diab_train_ever=0

replace diab_train_ever=1 if p207==1 & (p208==1 | p208==2)

*Collapse by facility

collapse (mean) diab_train_24 diab_train_ever, by(facil)

*recode so any facility with at least one staff member trained is coded as 1

recode diab_train_24 0.0001/1=1

recode diab_train_ever 0.0001/1=1

sort facil

save "BPdiabprov.dta", replace

*Merge the collapsed provider file with the facility file

merge 1:1 facil using "BDFC7IFLSP.dta"

*Generate a code for facilities which have any diabetes services

gen anydiabserv=0

replace anydiabserv=1 if inrange(q2301,1,3)

*Code guidelines variable

gen guidelines=0

replace guidelines=1 if q2303==1 | q2305==1

*Generate weight variables for facilities

gen fwt = facwt/1000000

egen strata = group(factype region)

svyset [iw=fwt], psu(facil) strata(strata) singleunit(centered)

*Proportions below are the same as in the "total" row in table 8.1 final report

svy: tab guidelines if anydiabserv==1

svy: tab diab_train_24 if anydiabserv==1

svy: tab diab_train_ever if anydiabserv==1

*To exclude CCs, just recode the factype variable to exclude the CCs, and tab the variables of interest by the recoded variables

I hope this is helpful for your analysis.

Best,
Sara
