
Subject: Re: Creating some variables

Posted by [SaraDHS](#) on Sat, 09 Mar 2024 11:38:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

You were getting close, but some of the conditional statements were slightly off. I have added the correct code below and commented out your earlier code.

Best,

Sara

*Sterilization equipment

```
gen ste=0  
replace ste=1 if (q201==1 | q201==2) & ((q501a_03==1 & q501b_03==1) | (q501a_01==1 &  
q501b_01==1) | (q501a_02==1 & q501b_02==1 & q501a_06==1 & q501b_06==1))  
tab ste [iw=wt]
```

/*gen ste=0

```
replace ste=1 if (q201==1 | q201==2) & ((q501a_04==1 & q501b_04==1) | (q501a_01==1 &  
q501b_01==1) | (q501a_02==1 & q501b_02==1 & q501a_07==1 & q501b_07==1))  
tab ste [iw=wt]  
*/
```

*Equipment for high level disinfection

```
gen hilvldis=0  
replace hilvldis=1 if (q201==1 | q201==2) & ((q501a_04==1 & q501b_04==1) | (q501a_05==1 &  
q501a_06==1 & q501b_06==1) | (q501a_09==1 & (regexm(q502g_5,"C") | regexm(q502g_5,"D") |  
regexm(q502g_5,"E") | regexm(q502g_5,"F"))))  
tab hilvldis [iw=wt]
```

/*gen hilvldis=0

```
replace hilvldis=1 if (q201==1 | q201==2) & ((q501a_4==1 & q501b_4==1) | (q501a_5==1) |  
(q501a_9==1 & inrange(q502g_5,3,5)))  
tab hilvldis [iw=wt]  
*/
```

*Client latrine

gen latrine=0

```
*replace latrine=1 if (q620==11|q620==12)&(q620==21)|(q620==22|q620==31)  
replace latrine=1 if q620==11 | q620==12 | q620==13 | q620==14 | q620==15 | q620==21 |  
q620==22 | q620==31  
label var latrine "client latrine"  
tab latrine [iw=wt],m
```
