
Subject: Re: Clustered Standard Errors

Posted by [Bridgette-DHS](#) on Wed, 02 Mar 2016 16:57:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

Following is a response from Senior DHS Stata Specialist, Tom Pullum:

Yes, if you construct svyset as you say, and then put "svy: " in front of an estimation command, you will get robust standard errors.

You can make the cluster adjustment in two ways. One is with svyset, the other is with regress y x, cluster(v021). (I think you meant to put "cluster(v021)" rather than "cluster(ADM1_CODE)".)

You can make the weight adjustment in two ways. One is with svyset, the other is with regress y x [pweight=v005].

You can also do regress y x [pweight=v005], cluster(v021).

You cannot, however, include the stratum adjustment within an estimation command. That adjustment can ONLY be made with svyset.

Note that v001 and v021 are exactly the same.

Something has gone wrong with v024 in your DRC 2007 data file. I expect that it has been recoded incorrectly. A conspicuous warning that something was wrong is the huge number of cases in the lines with labels.

I don't know which of the DRC 2007 files you are using, but here are the codes for the PR file

```
. label list hv024
```

```
hv024:
```

```
 10 kinshasa
 20 bas-congo
 30 bandundu
 40 equateur
 50 orientale
 61 nord-kivu
 62 maniema
 63 sud-kivu
 70 katanga
 80 kasa-oriental
 90 kasa-occident
```

In the PR file, the total household population is 48,291. You are way off.
