Subject: Injuries

Posted by Anne on Wed, 20 Apr 2022 16:38:06 GMT

View Forum Message <> Reply to Message

Hello,

I would like to be able to get similar results (for deaths and injuries) to what is in the tables 2.18 and 2.21 for road traffic accidents and non-road traffic injuries respectively. But am not sure which database to use. For instance, the total population in both tables is 87,929 so I tried to use the UGPR7BFL file which has 91,167 observations.

But when I tabulate the variable for death related to traffic accidents (sa06) or the death related to the incident (sa17), everything is missing.

Your guidance on this will be highly appreciated.

Many thanks, Anne

Subject: Re: Injuries

Posted by Janet-DHS on Fri, 22 Apr 2022 13:10:21 GMT

View Forum Message <> Reply to Message

Following is response from DHS Research & Data Analysis Director, Tom Pullum:

The number 87,929 is the weighted number of de facto residents. Open the PR file with Stata and enter this line "tab hv102 hv103 [iweight=hv005/1000000]". You will get the following table:

. tab hv102 hv103 [iweight=hv005/1000000]

You see 87,929 as the (weighted and rounded) total in the second column. This is like a population total for the denominator of a death rate. All of the numbers in the last column of tables 2.18 and 2.21 come from the PR file and serve as the denominators of the rates in the rows of those tables.

However, none of these people died before the survey, because of traffic accidents or anything else. (Some people may have been injured.) To get at deaths or injuries you have to go to the HR file. In general if something was included in the survey and you simply can't find it anywhere else,

you can check the HR file, which has one record per household, and you may find it there.

Open the HR file and enter the following lines in Stata:

keep hv001 hv002 hv005 sa\*\_\*

reshape long saidxa\_ sa04\_ sa05\_ sa06\_ sa06a\_ sa07\_ sa08\_ sa09\_ sa10a\_ sa10b\_ sa10c\_ sa10d\_ sa10e\_ sa10f\_ sa10g\_ sa10h\_ sa10i\_ sa10j\_ sa10k\_ sa10l\_ sa10x\_ saidxi\_ sa15\_ sa16\_ sa17\_ sa17a\_ sa18\_ sa19\_ sa20\_ sa21a\_ sa21b\_ sa21c\_ sa21d\_ sa21e\_ sa21f\_ sa21f\_ sa21f\_ sa21h\_ sa21i\_ sa21i\_ sa21k\_ sa21l\_ sa21x\_ sa26\_ sa27\_ sa28\_ sa29\_ sa30\_ , i(hv001 hv002) j(case)

rename \* \*

tab saidxa,m drop if saidxa==.

In the reshape step the labels will be lost and you need to re-attach them, but otherwise this gives you a file of the deaths and injuries. You can use it to construct the numerators of the rates (be sure to weight with hv005). The rates are constructed as 100,000\*numerator/denominator.

There are more elegant ways to get this file but this way should work. Let us know if you have other questions.