
Subject: Reshaping data using Stata
Posted by [Mercysh](#) on Fri, 05 Dec 2014 07:22:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

I would appreciate some help regarding reshaping of the variables b16_01 to b16_20 (from individual datasets) so that I have one variable that I can compare with hv112 (from PR file), for mothers reported to be on the household schedule and whose children are younger than 18 years. I have followed a few examples but not getting it right.

Subject: Re: Reshaping data using Stata
Posted by [Bridgette-DHS](#) on Tue, 16 Dec 2014 15:04:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Your post is being reviewed by a DHS moderator, and someone will respond soonest.

Thanks for your patience.

Subject: Re: Reshaping data using Stata
Posted by [Trevor-DHS](#) on Tue, 16 Dec 2014 17:40:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

I would suggest starting with the Births Recode (BR) dataset, rather than the IR dataset, as that file is already reshaped.

If you want to reshape the file you can use something like:
use "NGIR6AFL.DTA"

* keep the variables of interest, e.g.

* If you don't limit the number of variables, the reshape is really, really slow.

keep caseid v000 v005 v008 v013 v201 b*

* Rename all of the repeating variables to drop the leading 0 to help with reshaping

rename b*_0* b*_*

* Reshape the file into a sibling history file

* This will be slow to run and could take 5 minutes or more.

reshape long bidx_ bord_ b0_ b1_ b2_ b3_ b4_ b5_ b6_ b7_ b8_ b9_ b10_ b11_ b12_ b13_ b15_ b16_, i(caseid) j(bindex)

* Rename to drop the trailing underscore on the end of the reshaped variables

rename b*_ b*

* Drop empty entries

drop if bidx==.

Subject: Re: Reshaping data using Stata
Posted by [vkyini](#) on Sat, 11 Feb 2023 11:44:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

I'm working on IR file, I want to use only the b5_ variable, and in India DHS, it ranges from b5_01 to b5_20.

So my query is how to reshape it.

I'm trying to do it with the codes given as

```
reshape long b5_ , i(caseid) j(bindex)
```

But it is not giving the correct results when I'm checking it with couple file(where b5 is directly given), I tried this code also

```
reshape long b5_0 , i(caseid) j(bindex)
```

but here, the j goes from 0 to 9 only.

Please help me with this.

Subject: Re: Reshaping data using Stata

Posted by [vkyini](#) on Sat, 11 Feb 2023 12:23:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

Sorry for the concern. There was some issue with my system; the code is working.

Thank you
